



Temcoat™



Temcoat applied to pipe surface. It will then be wrapped with Poly-Ply™, Guard-Wrap™ or Wax-Tape®.

Description:

Temcoat™ is a high-temperature microcrystalline wax-based coating compound that will not melt and can be applied at ambient temperatures up to 200 °F. It does not require a primer or curing time and is easily applied by hand.

End Use:

Temcoat is used as an anticorrosion compound for aboveground, underground and underwater metal surfaces. It is used as a coating with a wrapper or as a priming paste with Wax-Tape® systems. Because of its paste consistency over a wide temperature range, it is an excellent material for filling voids in both systems. It can be used for straight pipe, irregular fittings and flat surfaces.

Application Procedures:

Wire brush and wipe the surface clean of any loose coating, rust, scale and foreign matter. Then, apply Temcoat by hand directly to the surface. At higher temperatures Temcoat can be applied by brush. On wet surfaces, rub and press firmly to displace moisture and ensure adhesion.

When used on underground applications, to protect Temcoat from mechanical abrasion, overwrap with appropriate wrapper such as Poly-Ply™, Guard-Wrap™ or #1 Wax-Tape®. For aboveground or vaults overwrap with #2 Wax-Tape®.

Packaging:

3-gallon pails (approx. 24 lbs/pail)
1-gallon cans (4 gallons/case) 32 lbs/case

Specifications:

Color	Brown
Pour point	non-melting
Flash point	350 °F (minimum)
Dielectric strength	100 volts per mil
Application temperature	32 ° -200 ° F

Advantages:

- Withstands high ambient temperatures
- Goes on easily by hand
- No primer required
- No waiting for drying or curing
- Nonhazardous, no VOCs
- Minimal surface preparation
- Can be applied to wet pipe
- Supports cathodic protection



Corporate Office:

7700 Jackson Road
Ann Arbor, MI 48103 USA
(734) 424-3600
Fax: (734) 426-5882
trenton@trentoncorp.com

Export/Houston Office:

1880 S. Dairy Ashford Rd.
Suite #697
Houston, Texas 77077 USA
(281) 556-1000
Fax: (281) 556-1122
tweber@trentoncorp.com

European Office:

8, rue de Berri
Paris, France 75008
+33 (0) 1 42 99 95 78
Fax: +33 (0) 1 42 99 95 79
europe@trentoncorp.com

www.trentoncorp.com